



FM8119

FM8119

FM8119

- USB
- 4
- 8
- 108K 40%
- 2uA@3.7V
- ASIC
- SOP-8

FM8119

FM8119


FM8119	SOP-8
--------	-------

FM8119

<p>SOP-8</p>	1	VCC	
	2	TIME	
	3	KEY	
	4	GND	
	5	PH	
	6	WLED	
	7	CLED	
	8	BAT	



FM8119



- 1 PCB L1 BAT BAT
- L1 25 800uH
- 2 USB BAT
- FM8119 (1)

BAT		-0.3 +5.5	V
VCC		-0.3 +5.5	V
WLED/CLED	LED	-0.3 +5.5	V
TOPR		-20 +120	
TSTG		-40 +150	
	ESD (2)	4000	V
	5	+265	

- 1
- 2 ESD
- ESD 100pF 1.5KΩ



FM8119

	WLED	2	
		20	

1		4H	
2		8H	
3			

FM8119

Vbat=3.7V,T=25

Vbat			4.5	5.0	5.5	V
Vuvlo		Bat		3.0		V
Tmax		TIME="1"	1	4		H
		TIME="1"	2	8		H
Iq		Vbat=3.7V		2		uA
Vthmin				2.4		V
WLED	WLED	LED		10		mA

FM8119

FM8119

MCU

ASIC

2uA

LED

LED

FM8119

LED

BG

I_BIAS

OSC

1

(<2uA)

FM8119

2uA,

2

3

FM8119

(UVLO),
WLED

20

3.0V


UVLO

ChipSourceTek



FM8119

> SOP-8



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	-	1.50	1.55
A1	-	0.10	0.15
A2	1.35	1.40	1.45
A3	0.55	0.60	0.65
b	0.35	0.40	0.45
c	0.17	0.22	0.25
D	4.85	4.90	4.95